

DECLARATION OF CONFORMITY CE

ALELUIA, Cerâmicas S.A.

Adress of the Manufacture and Place of Production:

Quinta do Simão – Esgueira

3801-101 – Aveiro – Portugal

Apartado 3024

Telephone : + 351 234 305 600 Fax + 351 234 305 699


Email: geral@aleluia.pt

Dry-pressed ceramic wall tiles

Group B III (European Standard EN 14411 - Annex L) GL

End uses: Internal walls

Glazed wall tiles (Size 25x36)

 05	EN 14411: 2006 - Group B III (Annex L) GL Type of Tile: Dry-Pressed Ceramic Wall tiles End Uses: Internal walls ALELUIA, CERÂMICAS S. A. Aveiro - Portugal	
List of the Characteristics	Declared Values	Test Method
Reaction to Fire	Class A1	Without Testing 96/603/CE
Flexural tensile Strenght	Breaking Strenght ≥ 600 N	EN ISO 10545 - 4
	Modulus of Rupture ≥ 13 N / mm ²	EN ISO 10545 – 4
Release of Dangerous substances (Cd e Pb)	NPD	-----
Bond Strenght / Adhesion	a) With Cementitious Adhesives 1,4 N/mm ² b) With Dispersion Adhesives 2,5 N/mm ² c) With Resin Adhesives 7 N/mm ² d) With Mortar 0,7 N/mm ²	a) EN 1348 Clause 8.2 b) EN 1324 Clause 7.2 c) EN 12003 Clause 7.2 d) EN 1015 - 12

This declaration is completely according with the established on the European Standard EN 14411 and the annex ZA (ZA.3)



Elmano Castilho
(Quality Manager)