

DECLARATION OF CONFORMITY CE

ALELUIA, Cerâmicas S.A.

Adress of the Manufacture:

Quinta do Simão – Esgueira

3801-101 – Aveiro – Portugal

Apartado 3024

Telephone : + 351 234 305 600 Fax + 351 234 305 699

Email: geral@aleluia.pt

Place of Production:

Zona Industrial da Mota – Apartado 32

3834-909 – Ílhavo – Portugal


Telephone: + 351 234 329 900 Fax + 351 234 329 901

Dry-pressed ceramic wall tiles


Group B III (European Standard EN 14411 - Annex L) GL

End uses: Internal walls

Glazed wall tiles (Size 32,7x58,6 Rectified)

|  05 EN 14411: 2006 - Group B III (Annex L) GL Type of Tile: Dry-Pressed Ceramic Wall tiles End Uses: Internal walls ALELUIA, CERÁMICAS S.A. Aveiro - Portugal | | |
|--|---|---|
| List of the Characteristics | Declared Values | Test Method |
| Reaction to Fire | Class A1 | Without Testing 96/603/CE |
| Flexural tensile Strenght | Breaking Strenght ≥ 600 N | EN ISO 10545 - 4 |
| | Modulus of Rupture ≥ 13 N / mm ² | EN ISO 10545 – 4 |
| Release of Dangerous substances (Cd e Pb) | NPD | ----- |
| Bond Strenght / Adhesion | a) With Cementitious Adhesives 1,4 N/mm ² b) With Dispersion Adhesives 2,5 N/mm ² c) With Resin Adhesives 7 N/mm ² d) With Mortar 0,7 N/mm ² | a) EN 1348 Clause 8.2 b) EN 1324 Clause 7.2 c) EN 12003 Clause 7.2 d) EN 1015 - 12 |

This declaration is completely according with the established on the European Standard EN 14411 and the annex ZA (ZA.3)



Elmano Castilho
(Quality Manager)