

## DECLARATION OF CONFORMITY CE

### ALELUIA, Cerâmicas S.A.

Adress of the Manufacture:

Quinta do Simão – Esgueira

3801-101 – Aveiro – Portugal

Apartado 3024

Telephone : + 351 234 305 600 Fax + 351 234 305 699

Email: geral@aleluia.pt

Place of Production:

Zona Industrial da Mota – Apartado 32

3834-909 – Ílhavo – Portugal


Telephone: + 351 234 329 900 Fax + 351 234 329 901

**Dry-pressed ceramic wall tiles**


**Group B III (European Standard EN 14411 - Annex L) GL**

**End uses: Internal walls**

**Glazed wall tiles (Size 33,3x42,9)**

 <b>05</b>		
<b>EN 14411: 2006 - Group B III (Annex L) GL</b> <b>Type of Tile: Dry-Pressed Ceramic Wall tiles</b> <b>End Uses: Internal walls</b> <b>ALELUIA, CERÁMICAS S.A.</b> <b>Aveiro - Portugal</b>		
List of the Characteristics	Declared Values	Test Method
Reaction to Fire	Class A1	Without Testing 96/603/CE
Flexural tensile Strenght	Breaking Strenght ≥ 600 N	EN ISO 10545 - 4
	Modulus of Rupture ≥ 13 N / mm <sup>2</sup>	EN ISO 10545 – 4
Release of Dangerous substances (Cd e Pb)	NPD	-----
Bond Strenght / Adhesion	a) With Cementitious Adhesives 1,4 N/mm <sup>2</sup> b) With Dispersion Adhesives 2,5 N/mm <sup>2</sup> c) With Resin Adhesives 7 N/mm <sup>2</sup> d) With Mortar 0,7 N/mm <sup>2</sup>	a) EN 1348 Clause 8.2 b) EN 1324 Clause 7.2 c) EN 12003 Clause 7.2 d) EN 1015 - 12

**This declaration is completely according with the established on the European Standard EN 14411 and the annex ZA (ZA.3)**



Elmano Castilho  
(Quality Manager)